


# Linear Led Karo x4

AVOLUX®



## Electrical Parameters

<b>Base Model No.:</b>	<b>LL.I02.LL.19725</b>
Colours:	White, black, silver
Wattage:	38W
CCT:	2700K - 5000K
IP Rating:	IP 20
Beam Angle:	105°
CRI:	Ra+80

## Features

- Sheet steel body.
- Microprismatic PMMA opal diffuser.
- Only to be used with electronic Led Driver.
- Mains voltage: 220-240V / 50-60Hz.
- 1-10V and DALI dimming options available upon request.
- Over 100%/W efficiency.
- An emergency kit system can be integrated.
- Designed for T-Bar ceilings.
- Electronic LED driver positioned outside of the luminaire and connected with wieland connector.

## Specifications

Model	Wattage	CCT	Lumens	Colour	Beam Angle
LL.I02.LL.19725.40-WH/3/105	38W	3000K	4600lm	White	105°
LL.I02.LL.19725.40-WH/3.5/105	38W	3500K	4700lm	White	105°
LL.I02.LL.19725.40-WH/4/105	38W	4000K	4800lm	White	105°
LL.I02.LL.19725.40-GR/3/105	38W	3000K	4600lm	Grey	105°
LL.I02.LL.19725.40-GR/3.5/105	38W	3500K	4700lm	Grey	105°
LL.I02.LL.19725.40-GR/4/105	38W	4000K	4800lm	Grey	105°
LL.I02.LL.19725.40-BL/3/105	38W	3000K	4600lm	Black	105°
LL.I02.LL.19725.40-BL/3.5/105	38W	3500K	4700lm	Black	105°
LL.I02.LL.19725.40-BL/4/105	38W	4000K	4800lm	Black	105°