


Linear Led Systema Low Glare louver

AVOLUX®



Electrical Paramaters

Base Model No.:	LL.I02.LL.19450
Colours:	White, black, silver
Wattage:	51W
Lenght:	1510mm
CCT:	2700K - 5000K
IP Rating:	IP 20
Beam Angle:	70°
CRI:	Ra+80

Features

- Aluminium profile body.
- Plastic end caps.
- Only to be used with electronic Led Driver.
- Mains voltage: 220-240V / 50-60Hz.
- 1-10V and DALI dimming options available upon request.
- Dense Louver reflector structure aiming to minimise UGR.
- Over 100%/W efficiency.
- An emergency kit system can be integrated.

Specifications

Model	Wattage	CCT	Lumens	Colour	Beam Angle
LL.I02.LL.19450.55-WH/3/70	51W	3000K	7000lm	White	70°
LL.I02.LL.19450.55-WH/3.5/70	51W	3500K	7150lm	White	70°
LL.I02.LL.19450.55-WH/4/70	51W	4000K	7300lm	White	70°
LL.I02.LL.19450.55-GR/3/70	51W	3000K	7000lm	Grey	70°
LL.I02.LL.19450.55-GR/3.5/70	51W	3500K	7150lm	Grey	70°
LL.I02.LL.19450.55-GR/4/70	51W	4000K	7300lm	Grey	70°
LL.I02.LL.19450.55-BL/3/70	51W	3000K	7000lm	Black	70°
LL.I02.LL.19450.55-BL/3.5/70	51W	3500K	7150lm	Black	70°
LL.I02.LL.19450.55-BL/4/70	51W	4000K	7300lm	Black	70°