


Atlas Semi-recessed



20 W

2700K - 4000K

**Ra+80
Ra+90**

IP20



Electrical Parameters

Base Model No.:	LL.1042.22.01
LED Module:	Bridgelux Vero 18
Colours:	Several options
Wattage:	20.1W
Beam Angle:	22°, 45°, 58°
CCT:	2700K - 4000K, Class A
IP Rating:	Class III, IP 20
CRI:	Ra+80, Ra+90
Cutout Size:	95mm

Features

- High quality components.
- 2700K, 3000K, 4000K and Class A LED available.
- 3 Different beam angles possible.
- Very versatile LED downlight.
- Lots of color possibilities.
- Passive cooled, high power downlight.
- Compact design.
- Dimming options: 1-10V, Dali, Push, Touch.

Colours



Specifications

Model	Wattage	CCT/CRI	Luminous Flux	Lumens	Colour	Beam Angle
LL.1042.22.927.01	20.1W	2700K - Ra90	700 mA	1798 lm	White Matt	22°
LL.1042.22.830.01	20.1W	3000K - Ra80	700 mA	2314 lm	White Matt	22°
LL.1042.22.930.01	20.1W	3000K - Ra90	700 mA	1866 lm	White Matt	22°
LL.1042.22.840.01	20.1W	4000K - Ra80	700 mA	2457 lm	White Matt	22°
LL.1042.22.A30.01	20.1W	3000K - Class A	700 mA	1777 lm	White Matt	22°