

# Halo Sivo 1000mm

AVOLUX®



28w

2700K-5000K

Ra+80

IP20



## Electrical Parameters

|                        |  |
|------------------------|--|
| <b>Base Model No.:</b> | <b>LL.I02.II.13125</b>                 |
| LED Type:              | Philips (39), Tridonic (44), Cree (06) |
| Colours:               | White, Black, Grey                     |
| Wattage:               | 28W                                    |
| CCT:                   | 2700K - 5000K                          |
| IP Rating:             | IP 20                                  |
| Driver Voltage:        | 24V                                    |
| CRI:                   | Ra+80                                  |
| Sizes:                 | From 500mm to 2000mm                   |

## Features

- Aluminium body.
- Only to be used with electronic Led Driver.
- Mains voltage: 220-240V / 50-60Hz.
- 1-10V, DALI and switch dimming options available upon request
- High efficient opal diffuser.
- Basic colours: white, black, silver and special color options available upon request.
- Emergency kit system can be integrateg.

## Specifications

| Model                   | Wattage | CCT   | Lumens | Colour |
|-------------------------|---------|-------|--------|--------|
| LL.I02.II.13125.3000.WH | 28w     | 3000K | 3430lm | White  |
| LL.I02.II.13125.4000.WH | 28w     | 4000K | 3550lm | White  |
| LL.I02.II.13125.5000.WH | 28w     | 5000K | 3700lm | White  |
| LL.I02.II.13125.3000.GR | 28w     | 3000K | 3430lm | Grey   |
| LL.I02.II.13125.4000.GR | 28w     | 4000K | 3550lm | Grey   |
| LL.I02.II.13125.5000.GR | 28w     | 5000K | 3700lm | Grey   |
| LL.I02.II.13125.3000.BL | 28w     | 3000K | 3430lm | Black  |
| LL.I02.II.13125.4000.BL | 28w     | 4000K | 3550lm | Black  |
| LL.I02.II.13125.5000.BL | 28w     | 5000K | 3700lm | Black  |