

Titan Surface Mounted Spotlight



Electrical Parameters

Base Model No.:	LL.1204.90
LED Module:	Bridgelux Vero 10 LED
Colours:	Several options
Wattage:	9.3W
Beam Angle:	28°, 40°
CCT:	2700K - 3000K
IP Rating:	Class III, IP 20
CRI:	Ra+80, Ra+90
Cutout Size:	60mm

Features

- High efficiency LED downlight, surface mounted, equipped with a Bridgelux chip-on-board LED.
- Compact design with a tilt of 90 degrees.
- High Quality components.
- Available with wide beam or medium beam
- Standard supplied with Matt White Texture Powder-coating.
- Very long lifetime (L70B50 +50000hrs)
- High efficiency LED with many possibilities
- High Lumen output
- High CRI (>90) and great color consistency
- Easy installation

Colours



Specifications

Model	Wattage	CCT/CRI	Lumens	Colour	Beam Angle
LL.1204.90.2700.28.01	9.3W	2700K - Ra90	910 lm	White Matt	28°
LL.1204.90.3000.28.01	9.3W	3000K - Ra90	950 lm	White Matt	28°
LL.1204.90.2700.40.01	9.3W	2700K - Ra90	910 lm	White Matt	40°
LL.1204.90.3000.40.01	9.3W	3000K - Ra90	950 lm	White Matt	40°