



Leila Bridgespot

AVOLUX®



Electrical Paramaters

Base Model No.:	LL.I01.MLR.15072
Led Type:	Cree (06)
Colours:	White, black, silver
Wattage:	36W
Beam Angle:	73°
CCT:	2700K - 5000K
IP Rating:	IP 20
CRI:	Ra+80, Ra+90

Features

- Die-cast aluminium body.
- Only to be used with electronic Led driver.
- Mains voltage: 220-240V / 50-60Hz.
- Clever thermal design.
- 1-10V, DALI and switch dimming options available upon request.
- Clear safety glass.
- Wide beam angle 99.9% pure aluminium anodized reflector.
- Emergency kit system can be integrated.

Specifications

Model	Wattage	CCT	Lumens	Colour	Beam Angle
LL.I01.MLR.15072-WH/3/73	36W	3000K	780lm	White	73°
LL.I01.MLR.15072-WH/3.5/73	36W	3500K	795lm	White	73°
LL.I01.MLR.15072-WH/4/73	36W	4000K	810lm	White	73°
LL.I01.MLR.15072-GR/3/73	36W	3000K	780lm	Grey	73°
LL.I01.MLR.15072-GR/3.5/73	36W	3500K	795lm	Grey	73°
LL.I01.MLR.15072-GR/4/73	36W	4000K	810lm	Grey	73°
LL.I01.MLR.15072-BL/3/73	36W	3000K	780lm	Black	73°
LL.I01.MLR.15072-BL/3.5/73	36W	3500K	795lm	Black	73°
LL.I01.MLR.15072-BL/4/73	36W	4000K	810lm	Black	73°