

# Atlas Base Double Ceiling Light



## Electrical Parameters

<b>Base Model No.:</b>	<b>LL.1040.22.01</b>
LED Module:	2x Bridgelux Vero 18
Colours:	Several options
Wattage:	20.1W
Beam Angle:	22°, 45°, 58°
CCT:	2700K - 4000K, Class A
IP Rating:	Class I, IP 20
CRI:	Ra+80, Ra+90

## Features

- High quality components.
- 2700K, 3000K, 4000K and Class A LED available.
- 3 Different beam angles possible.
- Very versatile LED downlight.
- Lots of color possibilities.
- Passive cooled, high power downlight.
- Compact design.
- Dimming options: Dali

## Colours



## Specifications

Model	Wattage	CCT/CRI	Luminous Flux	Lumens	Colour	Beam Angle
LL.1040.22.927.01	(2x) 20.1W	2700K - Ra90	700 mA	(2x) 1798 lm	White Matt	22°
LL.1040.22.830.01	(2x) 20.1W	3000K - Ra80	700 mA	(2x) 2314 lm	White Matt	22°
LL.1040.22.930.01	(2x) 20.1W	3000K - Ra90	700 mA	(2x) 1866 lm	White Matt	22°
LL.1040.22.840.01	(2x) 20.1W	4000K - Ra80	700 mA	(2x) 2457 lm	White Matt	22°
LL.1040.22.A30.01	(2x) 20.1W	3000K - Class A	700 mA	(2x) 1777 lm	White Matt	22°